


Piastrella piena 40x40



Colours available:



Modular and draining tile for outdoor flooring, equipped with interlocking system that facilitates the installation and possible removal.

Technical data	
Dimensions	40 x 40 cm (1 m ² = 6,25 pz)
Material	Polypropylene (V0 UL94)
Thickness	3,3 cm
Loading capacity	Test: Pontarolo Engineering Valor: 24.000 kg/m ²
Thermal expansion coefficient*	0,05 - 0,2 mm/m° C

**Definition of the slip classification according to DIN 51130: 2014-02, according to BGR 181: 2003: values range from R9 (worst) to R13 (best). R10 corresponds to an average angle value of more than 10 years up to 19 years*

Piastrella features
Easy to install and remove thanks to the hooking system
Adapts to all project areas
Draining and non-slip surface
Does not require specific maintenance. Easy to clean
Made of 100% recycled and recyclable plastic

Piastrella piena 40x40

Applications

Ideal for: gardens, terraces and walkways; draining platforms on hard surfaces such as poolside, showers, camping, sports, music and trade fair
Uses: realization or renewal of outdoor flooring

Installation

Installation is simple, fast and does not require the use of special tools.

1. Start laying in the corner with the hooks always facing in the same direction.
2. Fit the male and female hooks under moderate pressure. Use a plastic mallet if necessary.
3. The tile joints shall have a hole allowing the floor to be fixed to the ground if necessary.
4. The laying of the floor can be completed with the appropriate accessories (curbs and corners).

Note: Tile sizes 40x40 and 60x60 are compatible with each other

Cleaning and maintenance

The product does not require specific maintenance. For cleaning it is recommended to wash Tile with the aid of a pressure washer at moderate pressure if the surrounding environment allows. Alternatively, use a damp cloth with a mild, non-aggressive neutral detergent; rub and rinse.

Warnings

- The support substrate must be a smooth, flat and rigid surface, not inclined and free of irregularities (such as pre-existing floors or raw concrete pulled to the surface). Any different use will be considered improper and does not give any right of objection.
- The materials with which the tiles are made can undergo expansion at different temperatures: it is therefore necessary to arrange a sufficient space along the perimeter of the flooring in order to allow the expansion and the natural movement of the elements.
- Carefully follow the instructions for installation and use. If installed otherwise than indicated, in particular on uneven substrate, the product may be subject to breakages that do not give the right to dispute.